

Our Pride, Packaging Your's

PACKAGING SOLUTIONS





AMAZON PLASTICS PVT LTD SURVEY NO.107/2/2/1,VILLAGE-NAROLI, SILVASSA-396230

SPECIFICATION INDEX AM/QCD/1501 CODE:20 L -A

	PACK SPECIFICAT	ION -20 LTR
	Product Code	20L-A-22500
CONTAINER	Product Type	Inner Lock
	Raw Matrial	РРСР
	Over Flow Capicity	22500 ML
	Maximum Filling Capacity	20 LTR
	Tare Weight	1035GM <u>+</u> 30GM
	Compression Strength	550 KGF (@ 10MM DEFLECTION)
	Drop Test Standard	Vertical on base -1.2m,Vertical on Lid 1.2m,Angular obase-1.2m,Horizontal-1.2m.
	Vibration Test Standard IS-7028 (Leakage Test)	Oil filled Packs are kept horizontally,vertically-uprigh vertically upside-down position on vibration tester,frequency,amplitude & duration of vibration a 120 CPM,25.4mm & 1 hr respectivery.
	Stacking	1+3
BODY	Colour	WHITE
	Height	380MM <u>+</u> 3MM
	Weight	759GM <u>+</u> 17 GM
	Top ID (Max)	291 MM <u>+</u> 2MM
	Top OD (Max)	325MM <u>+</u> 2MM
	Bottom OD	266MM <u>+</u> 2MM
	Wall Thickness (Min)	1.9MM <u>+</u> .002 MM
LID	Colour	WHITE
	Outer Diameter	315 MM <u>+</u> 1MM
	Height	34 MM <u>+</u> 1MM
	Weight (With Spout)	224GM <u>+</u> 8GM
HANDLE	Weight	52GM <u>+</u> 5 GM
	Material	METAL (MS WITH POWER COATED)
COMMUNICATION	Process	SCREEN PRINTING
	Desing & Colour reference	AS PER APPROVED DESING & PMSM SHADE CARD
	Print area (Length X Height)	835MM X 260MM
	Tape Teast	AS PER IS 10840:1994,ANNER E
SCOPE		



Amazon always aims at improving its productivity, quality and service. Amazon has served clients of all scales and potentials from varied industries, to establish itself as one of the most sought after supplier for every industrial packaging solution.

Get in touch now

Work:

Amazon Plastics Pvt Ltd, Survey Number: 107/2/2/1, Kannadi Phata, Opposite Bhilosa Industries, Dadra Nagar Haveli (UT) 396230.

Registered Office Address : Flat No. 33, Shiv Dham Building, 16th Santacruz Road, Opposite Gujarat Research Society, Santacruz West.

Email : info@amazonplasics.in

Phome : +91 8511 166623 / +91 9324 288421

www.amazonplastics.in